

Compare ThermoWorks Pocket-Digital Thermometers



	ThermoPop® 2 4.5 inch/8 inch	OutWard™	DASH™/DASH Mini™	Executive Series® EXEC®/ Mini®/Needle®	T-Grip™
Display					
Min/Max				✓	✓
Switch °C /°F	✓	✓	✓	✓	✓
Backlight	✓	✓	✓	✓	✓
Rotating Display	90° increments, Auto	180° Increments, Auto	180° Increments, Auto	180° Increments, Auto	180° Increments, Auto
Display Size	1.26 Inches diameter	0.7 H x 1.3 W Inches	0.7 H x 1.3 W Inches	0.45 H x 0.94 W Inches	0.70 H x 1.8 W inches
Hold				✓	
Probes					
Accuracy	to ±1.0°F (±0.5°C)	to ±0.9°F (±0.5°C)	to ±0.9°F (±0.5°C)	to ±0.9°F (±0.5°C)	to ±0.9°F (±0.5°C)
Temperature Range	-58 to 572°F (-50 to 300°C)	-58 to 572°F (-50 to 300°C)	-58 to 572°F (-50 to 300°C)	-40 to 572°F (-40 to 300°C)	-58 to 572°F (-50 to 300°C)
Probe Length	4.5 Inches or 8 Inches	4.5 Inches	4.5 Inches or 2.8 Inches	4.8 Inches or 2.9 Inches	5, 12, 24, or 36 Inches
Probe Diameter	0.10 Inch reduces to 0.06 Inch	0.09 Inch reduces to 0.06 Inch	0.12 Inch reduces to 0.08 Inch	0.1 Inch reduces to 0.06 Inch	0.2 or 0.24 Inch reduces to 0.14 Inch
Calibration Trim			✓	✓	✓
Housing					
Water Resistance	IP67	IP67	IP67	IP67	IP67
Warranty	2 years	2 years	2 years	5 years	2 years
Certification	NIST-traceable Certificate NSF	NIST-traceable Certificate NSF	NIST-traceable Certificate NSF	NIST-traceable Certificate NSF	NIST-traceable Certificate
Magnets & Lanyard			✓		
Colors	○●●●●●●●●	○●●●●●●●●	○●●●●●●●●	○●●●	○●●●
Power					
Battery Life (hrs.)	4,000 hours	5,000 hours	5,000 hours	3,000 hours	4,000 hours
Battery	1 x CR2032	1 x CR2032	1 x CR2032	1 x CR1632	1 x CR2032
Speed	2-3 seconds	2-3 seconds	3-4 seconds	3-4 seconds	8 seconds