

## Pro-Series High Temp Short Penetration Probe, 2.5"

Designed for use in commercial kitchens and professional settings, the Pro-Series Probes deliver better accuracy, faster readings, unique designs, wider temperature ranges and better moisture-resistance than probes sold with low-cost houseware-grade temperature alarms.

### Instructions, Tips and Cautions

- The cable may be closed in an oven door or under a BBQ hood using the precautions below.
- Do not pull on the cable. Use the molded mini-handle.
- The cable will withstand 700°F (370°C) for short periods.
- Probe tip itself is rated to 572°F (300°C). Do NOT expose probe tip to flames or coals.
- Construction is moisture-resistant but do not immerse.
- Keep the probe cable away from oven elements, flames, coals, grill or oven racks—all of which can reach temperatures far higher than 700°F (even if an oven is set lower). The probe cable can be damaged at higher temperatures. The inner insulation will melt and the probe will short (displaying "NO PROBE", LLL or HHH on the alarm display).
- Avoid repeated kinking or twisting of the probe cable which can break wires. To prolong the life of the probe, use a ThermoWorks Probe Spool.
- With care, the probe should last a long time. Eventually, you may need to replace it. If the probe becomes damaged, the base unit may flash "NO PROBE", LLL or HHH above the temperature display.



#### CABLE SHOULD AVOID:



Flames



Immersion



Racks



Coals



Elements



Kinks

### Specifications:

Cable Max Temp	700°F (370°C)
Transition Max Temp	644°F (340°C)
Probe Range	-58 to 572°F (-50 to 300°C)
Cable Length	47 inches (1.2m)
Probe Length	2.5 inches (63.5 mm)

### Technical Support

For warranty, service, and technical assistance, please contact ThermoWorks Technical Support at **(385) 330-0591** or email at [techsupport@thermoworks.com](mailto:techsupport@thermoworks.com).

Use only with ThermoWorks thermometers designed for the Pro-Series. Will not work in other brands.

**For additional cooking tips and doneness temperatures, and to see the full line of ThermoWorks tools, visit our website at [www.thermoworks.com](http://www.thermoworks.com).**

Copyright by ThermoWorks, Inc. Content may not be used in whole or in part without written consent. ThermoWorks, the ThermoWorks logo and Pro-Series are registered trademarks of ThermoWorks, Inc. All rights reserved.

**ThermoWorks, Inc.**

Utah, U.S.A.

Ph: 801-756-7705

Fax: 801-756-8948

[www.thermoworks.com](http://www.thermoworks.com)

P-17-010-01-b

Follow us on:



TX-1009X-ST

Pro-Series High Temp Short  
Penetration Probe, 2.5"

Designed in Utah.  
Assembled in China.

